



CATALOG NUMBER

TYPE

NOTES

ODLED-CP ODLED-CPR

Surface/Recessed Canopy with LED Modules

Product Description

12" x 12" Surface mount or 14" x 14" Recessed mount Canopy fixture with Lumen-Starr LED modules. LED diodes are recessed into an aluminum housing creating cooler operation, longer lamp life and higher lumen output.

Performance Summary

- *LED Diodes are 3W @ 200lm/Diode (Initial)
- *Average rated life (hr): >50,000
- *CRI: WW=85
CW =80
- *CCT: 3500K & 4100K
- *IP65

Power Supply

- *Class 2 Driver (Power Factor>99%, THD<10%, Efficiency>85%)
- *Operating Voltage: 120/277V
- *Output current: 750Ma max.

Specifications & Features

Light Emitting Diodes

- *LED technology delivers high quality white light.
- *Diodes designed to maintain 70% light output up to 50,000hrs.
- *Color management for controlled color consistency.

Construction

- *Die-Formed aluminum housing.
- *Post painted powder coating for long life finish.
- *Precision designed heat sink for cooler operation.

Ordering Information

ODLED-CP 407-60 - surface mount with LED Engine Module, 56W, 6000lm

ODLED-CPR 407-56 - surface/recessed mount with LED Engine Module, 56W, 6000lm



ODLED CPR407-56



ODLED CP407-60



Patented
LUMEN-STARR[®]
Technology



Montclair, Ca. 91763 USA
Tel: (909) 627-5333 Fax: (909) 627-2887
www.archipelagolighting.com