

RDI

Recessed Direct-Indirect T5 & T8 Troffers

Product Description

2x2 and 2x4 recessed, direct/indirect lay-in fixture, 5-1/2" deep. Fixtures offers general office lighting or general purpose usage.

Housing

Die-formed heavy gauge steel housing with high gloss white powder coat finish. Quick wire access included.

Electrical

Fully wired electronic ballast, 50/60hz with either dedicated 120V (MPF) or "universal" voltage 120/277V (HPF). UL and CUL listed. Standard fixture wiring is with single ballast operating all lamps. Inboard/outboard wiring with two ballast or master/slave also available.

Mounting

Grid or T-Bar mounting, individual or in continuous rows.

Ordering Information

Universal 120/277V (HPF)

- RDIT5 224 DV** - Recessed 2x2 Static Troffer w/2-24W T5 lamps
- RDIT5 324 DV** - Recessed 2x2 Static Troffer w/3-24W T5 lamps
- RDIT5 254 DV** - Recessed 2x4 Static Troffer w/2-54W T5 lamps
- RDIT5 354 DV** - Recessed 2x4 Static Troffer w/3-54W T5 lamps

- RDIT8 217 DV** - Recessed 2x2 Static Troffer w/2-17W T8 lamps
- RDIT8 317 DV** - Recessed 2x2 Static Troffer w/3-17W T8 lamps
- RDIT8 232 DV** - Recessed 2x4 Static Troffer w/2-32W T8 lamps
- RDIT8 332 DV** - Recessed 2x4 Static Troffer w/3-32W T8 lamps

Options

